

HHN-TSA/TSB/TSW/TSX

Sensor Terminal Block
传感器端子台



规格参数 SPECIFICATIONS

- 安装类型：导轨
- 接线方式：弹片式、螺钉式、MIL连接器
- 额定电流：0.5A
- 额定电压：24V
- 传感器输入类型：兼容NPN/PNP
- 输入端接口线径：28-16AWG/0.5-1.5mm²
- 输出端接口线径：22-12AWG/0.5-2.5mm²

- Installation type: rail
- Connection method: shrapnel type, screw type, MIL connector
- Rated current: 0.5A
- Rated voltage: 24V
- Sensor input type: compatible with NPN/PNP
- Input port interface wire diameter: 28-16AWG/0.5-1.5mm²
- Output port interface wire diameter: 22-12AWG/0.5-2.5mm²

外形尺寸 DIMENSIONS

路数 Number of Units	尺寸(长×宽×高) Dimensions (LxWxH)	型号(螺钉式) Model (screw type)	型号(弹片式) Model (shrapnel type)	型号(MIL连接器+螺钉式) Model (MIL connector + screw type)	型号(MIL连接器+弹片式) Model (MIL connector + shrapnel type)
4	53×60×36	TSA04/N	TSB04/N	TSW04/N	TSX04/N
6	53×60×36	TSA06/N	TSB06/N	TSW06/N	TSX06/N
8	68×60×36	TSA08/N	TSB08/N	TSW08/N	TSX08/N
12	97×60×36	TSA12/N	TSB12/N	TSW12/N	TSX12/N
16	117×60×36	TSA16/N	TSB16/N	TSW16/N	TSX16/N
24	172×60×36	TSA24/N	TSB24/N	TSW24/N	TSX24/N
4	53×60×36	TSA04/P	TSB04/P	TSW04/P	TSX04/P
6	53×60×36	TSA06/P	TSB06/P	TSW06/P	TSX06/P
8	68×60×36	TSA08/P	TSB08/P	TSW08/P	TSX08/P
12	97×60×36	TSA12/P	TSB12/P	TSW12/P	TSX12/P
16	117×60×36	TSA16/P	TSB16/P	TSW16/P	TSX16/P
24	172×60×36	TSA24/P	TSB24/P	TSW24/P	TSX24/P